

Balmerol® PRD Plus CF4 20W-40

Superior Quality Multigrade Crankcase Oil

Technical Data Sheet

Product Description:

Balmerol PRD Plus CF4 20W40 is designed as superior quality multigrade long drain crankcase oil for gasoline as well as diesel engines. Balmerol PRD Plus CF4 20W-40 is blended from selected base stocks and fortified with proprietary additive system to meet the performance level for different standards. Balmerol PRD Plus 20W40 has strong built in alkaline reserve to combat corrosive wear associated with the use of high sulfur fuels.

Balmerol PRD Plus CF4 20W-40 meets the following specifications:

- API – CD / CF
- Mack T 8A
- US Military MIL-L-2104 C performance levels
- IS: 13656 – 2002 Type EDL3

Balmerol PRD Plus CF4 20W-40 is manufactured based on Balmer Lawrie's proprietary **DEKATROL** technology.



Ten point advantage through balanced formulation

Features & Benefits:

Balmerol PRD Plus CF4 20W-40 provides the following benefits:

- Resists formation of hard piston deposits and varnish at high operating temperatures
- Reduces soft sludge formation associated with low engine temperatures in periodically idling conditions
- High protection against wear insuring maximum equipment life
- Extends oil drain period due to enhanced dispersancy
- Very good oxidation stability
- Reduces maintenance and operating costs

Applications / Recommendations:

- Recommended for use in turbo charged diesel engines, naturally aspirated diesel engines as well as heavy duty petrol engines.
- Suited for usage in extreme climatic conditions.

Balmerol® PRD Plus CF4 20W-40

Superior Quality Multigrade Crankcase Oil

Technical Data Sheet

Typical Properties:

Balmerol PRD Plus 20W-40	
Properties	PRD Plus 20W-40
Colour & Appearance	Clear & Bright
Viscosity, ASTM D 445, cst @ 100°C	14.5 - 16.0
Viscosity Index, min, ASTM D 2270	115
Pour Point, °C ASTM D 97	-21
Flash Point, (COC), °C, ASTM D 92	215
TBN, mg KOH/g, min, ASTM D 2896	10.0
Foam stability after 10 min. of settling time, quantity of foam, ml, max ASTM D892	
a) at 24 °C	Nil
b) at 93.5 °C	Nil
c) at 24 °C after test at 93.5 °C	Nil
Apparent Viscosity, cp at -20 °C, max. ASTM D5293	9500
Borderline pumping temperature (°C), max, ASTM D 3829	-20

Health and Safety:

Balmerol PRD Plus CF4 20W-40 is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. For MSDS please contact your local Balmer Lawrie Marketing / Technical Service team.

For Further Information, contact:

Balmer Lawrie & Co. Ltd.
SBU: Greases & Lubricants (G&L) Division
P- 43, Hide Road Extension
Kolkata: 700088
www.balmerlawrie.com